

DRIVING BELT AND TRANSVERSE ELEMENT FOR A DRIVING BELT

B > BACKGROUND OF THE INVENTION

The invention relates to a driving belt for use in a continuously variable transmission comprising two V-shaped pulleys, which driving belt comprises a carrier consisting of  
5 two endless band packages lying side by side, on which transverse elements are disposed, wherein each transverse element includes two recesses positioned opposite each other for receiving the band packages, so that a first part of the transverse element extends under said band packages, a second part of the transverse element is positioned between said band packages and a third part of the transverse element  
10 extends above said band packages, wherein the front side of the transverse element includes a projection which can mate with a recess in the adjacent transverse element.

> BACKGROUND OF THE RELATED ART

Such a driving belt is known from EP-A-0 014 013. The mating projection and recess ensure that transverse elements located adjacently to each other are correctly  
15 positioned with respect to each other during operation of the driving belt, especially in the straight part of the driving belt.

Each time a direction is described in relation to a transverse element, it is assumed that the transverse element occupies an upright position, as is shown in front elevation  
20 in Figure 2. In said figure, the longitudinal direction is the direction perpendicularly to the plane of the figure.

The provision of the projection, and of the corresponding recess that is located on the other side of the transverse element, takes place through deformation of the material,  
25 wherein a stamp forms the recess by moving into the material. This causes the material to be deformed to such an extent that said projection is formed on the other side of the transverse element.

This is a relatively difficult operation. It would be easier to realise a profile wherein the  
30 projection and the recess extend in horizontal direction. Such a profile can be formed by means of a rolling operation, for example, or by a grinding operation. When the transverse elements are cut from a strip of material, said strip of material can be provided with such a profile in advance.

0988394.051901  
T06T90.49EE880

Although a projection/recess, which extends in horizontal direction, has advantages when forming the same, it has become apparent in practice that such a projection/recess is not always satisfactory.

- 5 A projection and a recess which extend in horizontal direction have a surface which is substantially made up of a series of horizontal lines extending in transverse direction with respect to the driving belt.

B > SUMMARY OF THE INVENTION

- The object of the invention is to provide an improved driving belt, which driving belt is  
10 easier to manufacture and/or which operates more efficiently and/or more reliable.

Another object of the invention is to create a possibility to make the third part of the transverse element smaller, and thus lighter.

- 15 In order to accomplish that objective, said projection extends in horizontal direction, and wherein the rear side of the transverse element includes a recess which likewise extends in horizontal direction, wherein said projection and said recess are at least partially formed in the second part of the transverse element.
- 20 Said projection may be straight, but also elliptic or barrel-shaped.

- By forming the projection at least partially in the second part of the transverse element, the length of the projection (its dimension in horizontal direction) at least at the bottom side of the projection is limited to the width of the aforesaid second part. In practice it  
25 has become apparent that this enables the driving belt to function better than in the situation wherein the projection extends over the entire width of the transverse element, that is, wherein the projection is formed in a part of the transverse element that is considerably wider than said second part.

- 30 From US-A-3,949,621 it is known per se to form the projection in the second part of the transverse element. The projection that is used therein, however, is a projection which is round when seen in front view, that is, said projection does not extend in horizontal direction. The consequence is, therefore, that the second part must have a considerable width in order to make it possible to form the projection therein. The fact  
35 of the matter is that sufficient material must be present around the projection to be

0903364-061901

formed in order to enable correct deformation of material upon formation of the projection.

5 Preferably, said projection and said recess are present in large part in the second part of the transverse element, and more preferably said projection and said recess are mainly present in the second part of the transverse element. Owing to the limited length (in horizontal direction) of the projection and the recess, the connection that is thus obtained between transverse elements positioned adjacently to each other appears to function well in practice.

10

Preferably, said projection and said recess extend in transverse direction over the entire area of the transverse element between the two recesses.

15

Preferably, said projection is disposed some distance above the tilting line, which is the horizontally extending area of the surface of the transverse element that is constantly in contact with the adjacent transverse element. The tilting line is located under the band packages, and it is formed by a rounded corner in the surface of the transverse element.

20

Preferably, said projection is spaced from the tilting line by a distance, which is smaller than the smallest vertical dimension of the recess.

25 In one embodiment, the surface of the projection and of the recess comprises parts which extend at an angle to a horizontal line in the plane in which the band packages lie, and which extends perpendicularly to the direction of the driving belt. When such a part of the projection mates with a corresponding part of the recess, it is possible to reduce the extent to which two abutting transverse elements can move in horizontal direction relative to each other. In that case the surface of the projection and the recess is not entirely made up of a collection of horizontal lines, but it comprises a part  
30 that is different therefrom. Preferably, such a part of the projection is in the form of a recess in the surface, which recess preferably extends in vertical direction, as will be explained in more detail by means of an exemplary embodiment.

35 In another preferred embodiment, said third part of the transverse element comprises the aforesaid parts, which extend at an angle to the aforesaid line.

00003364-061901  
T06T90-19EE0060

Preferably, the transverse element is made from a strip of material by means of a cutting operation, and the edges of the transverse element have been deburred and/or been rounded by means of a tumbling operation, wherein the surface of the transverse elements is worked with hard elements.

The invention furthermore relates to a transverse element for use in a driving belt for a continuously variable transmission comprising two V-shaped pulleys, which transverse element includes two recesses positioned opposite each other for receiving band packages forming a carrier, so that a first part of the transverse element extends under said band packages, a second part of the transverse element is positioned between said band packages and a third part of the transverse element extends above said band packages, wherein each recess includes an inside surface facing towards the band package, wherein said projection extends in horizontal direction, and wherein the rear side of the transverse element includes a recess which likewise extends in horizontal direction, wherein said projection and said recess are at least partially formed in the second part of the transverse element.

In order to explain the invention more fully, an exemplary embodiment of a driving belt will be described hereafter with reference to the drawing.

## B > BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a schematic side view of a driving belt;  
Figure 2 is a front view of a transverse element;  
Figure 3 is a side view of the transverse element;  
Figure 4 is a rear view of the transverse element; and  
Figure 5 is a view of a detail of Figure 4.

## B > DESCRIPTION OF THE PREFERRED EMBODIMENTS

The schematic illustration of Figure 1 shows the driving belt 1, which runs over two pulleys 2, 3. In the illustrated situation, the left-hand pulley 2 rotates faster than the right-hand pulley 3. By changing the mutual distance between the two parts of which each pulley 2, 3 consists, it is possible to change the radius of the driving belt 1 at the location of pulley 2, 3, as a result of which the difference in speed between the two pulleys 2, 3 can be varied as desired. This is a well-known way of varying a difference in rotational speed between two shafts.

The driving belt 1, which is shown in side elevation in Figure 1, is built up of a plurality of transverse elements 4 (four of which are shown in Figure 1) and two band packages 5, 6, one of which is indicated by the shaded part in the figure. Both the transverse elements 4 and the bands of the band packages 5, 6 are made of a metal. The transverse elements 4 can move freely in the longitudinal direction of the band packages 5, 6, so that when a force is being transmitted between pulleys 2, 3, said force is transmitted by the transverse elements 4 pressing one against another. The band packages guide the transverse elements 4 thereby.

10 In the illustrated embodiment, each band package 5, 6 consists of five bands, as is shown in Figure 2. In practice, a band package 5, 6 frequently comprises more bands, for example ten. In Figure 2, the thickness of the band package 6 is indicated at T and the width is indicated at W. The thickness of a band is 0.2 mm, for example, with the width being 7 mm.

15 It will be apparent that the band packages 5, 6 cannot move out laterally, because parts of the pulleys 2, 3 are positioned on either side of the driving belt 1. From the figures it is apparent that the shape of transverse elements 4 has been selected so that said transverse elements are retained in position by the band packages 5, 6. Said shape comprises two recesses 7, 8, in which the band packages 5, 6 are accommodated.

20 Transverse element 4 consists of a first part 11, which extends under band packages 5, 6, a second part 12, which is located under band packages 5, 6, and a third part 13, which extends above band packages 5, 6.

25 The rear side of transverse element 4 (shown in Figure 4) is substantially flat, and on its front side (shown in Figure 2), transverse element 4 exhibits a so-called tilting line 18. The part of transverse element 4 above tilting line 18 has a substantially constant thickness, seen in side elevation (Figure 3), whilst the first part 11 under tilting line 18 tapers off in downward direction. Tilting line 18 is in fact formed by a slightly rounded strip on the front side of transverse element 4, for example by an edge having a radius of curvature of 6 mm. Tilting line 18 is in contact with the rear side of the adjacent transverse element 4, both in the straight parts of driving belt 1 and in the curved parts thereof.

T06T90"49EE8880

Below tilting line 18, first part 11 tapers off to an edge 26 extending in horizontal direction. First part 11 below edge 26 exhibits a constant thickness, which is about 0.1 mm less than the thickness of transverse element 4 just above edge 26.

5

As can be seen in particular in Figure 3, the second part 12 of transverse element 4 is shifted to the left (in Figure 3), as a result of which a projection 14 is formed on the front side of transverse element 4, whilst a recess 15 is present on the rear side. As is apparent from Figures 2 and 4, projection 14 and recess 15 extend in horizontal direction over the entire second part 12 of transverse element 4.

10

Projection 14 and recess 15 interlock in the straight parts of driving belt 1, as a result of which two abutting transverse elements 4 are prevented from shifting relative to each other.

15

As Figure 2 shows, projection 14 is centrally provided with a recessed part 16, and Figure 4 shows that recess 15 is centrally provided with a projecting part 17. In this manner, the surfaces of projection 14 and recess 15 include parts which extend at an angle to a horizontal line in the plane in which band packages 5, 6 lie, and which extends perpendicularly to the direction of driving belt 1.

20

In a straight part of the driving belt 1, the projecting part 17 comes into engagement with the recessed part 16, so that relative movement of two transverse elements 4 lying adjacently to each other is reduced or prevented altogether as a result of said parts including an angle coming into contact with each other.

25

As appears from the figures, projection 14 and recess 15 are located entirely in the second part 12 of transverse element 4, as a result of which their dimension in transverse direction (horizontal direction) is limited.

30

Each of the recesses 7, 8 is bounded by an inside surface that is formed by portions of first part 11, second part 12 and third part 13 of transverse element 4. Said portions are indicated by numerals 21, 22 and 23, respectively, in Figure 5.

00003364.061904  
T06T90.49EE8860

5

10

15

20

25

30

35

1. **Introduction**  
 2. **Background**  
 3. **Methodology**  
 4. **Results**  
 5. **Discussion**  
 6. **Conclusion**  
 7. **References**  
 8. **Appendix**  
 9. **Figure 1**  
 10. **Figure 2**  
 11. **Figure 3**  
 12. **Figure 4**  
 13. **Figure 5**  
 14. **Figure 6**  
 15. **Figure 7**  
 16. **Figure 8**  
 17. **Figure 9**  
 18. **Figure 10**  
 19. **Figure 11**  
 20. **Figure 12**  
 21. **Figure 13**  
 22. **Figure 14**  
 23. **Figure 15**  
 24. **Figure 16**  
 25. **Figure 17**  
 26. **Figure 18**  
 27. **Figure 19**  
 28. **Figure 20**  
 29. **Figure 21**  
 30. **Figure 22**  
 31. **Figure 23**  
 32. **Figure 24**  
 33. **Figure 25**  
 34. **Figure 26**  
 35. **Figure 27**  
 36. **Figure 28**  
 37. **Figure 29**  
 38. **Figure 30**  
 39. **Figure 31**  
 40. **Figure 32**  
 41. **Figure 33**  
 42. **Figure 34**  
 43. **Figure 35**  
 44. **Figure 36**  
 45. **Figure 37**  
 46. **Figure 38**  
 47. **Figure 39**  
 48. **Figure 40**  
 49. **Figure 41**  
 50. **Figure 42**  
 51. **Figure 43**  
 52. **Figure 44**  
 53. **Figure 45**  
 54. **Figure 46**  
 55. **Figure 47**  
 56. **Figure 48**  
 57. **Figure 49**  
 58. **Figure 50**  
 59. **Figure 51**  
 60. **Figure 52**  
 61. **Figure 53**  
 62. **Figure 54**  
 63. **Figure 55**  
 64. **Figure 56**  
 65. **Figure 57**  
 66. **Figure 58**  
 67. **Figure 59**  
 68. **Figure 60**  
 69. **Figure 61**  
 70. **Figure 62**  
 71. **Figure 63**  
 72. **Figure 64**  
 73. **Figure 65**  
 74. **Figure 66**  
 75. **Figure 67**  
 76. **Figure 68**  
 77. **Figure 69**  
 78. **Figure 70**  
 79. **Figure 71**  
 80. **Figure 72**  
 81. **Figure 73**  
 82. **Figure 74**  
 83. **Figure 75**  
 84. **Figure 76**  
 85. **Figure 77**  
 86. **Figure 78**  
 87. **Figure 79**  
 88. **Figure 80**  
 89. **Figure 81**  
 90. **Figure 82**  
 91. **Figure 83**  
 92. **Figure 84**  
 93. **Figure 85**  
 94. **Figure 86**  
 95. **Figure 87**  
 96. **Figure 88**  
 97. **Figure 89**  
 98. **Figure 90**  
 99. **Figure 91**  
 100. **Figure 92**  
 101. **Figure 93**  
 102. **Figure 94**  
 103. **Figure 95**  
 104. **Figure 96**  
 105. **Figure 97**  
 106. **Figure 98**  
 107. **Figure 99**  
 108. **Figure 100**  
 109. **Figure 101**  
 110. **Figure 102**  
 111. **Figure 103**  
 112. **Figure 104**  
 113. **Figure 105**  
 114. **Figure 106**  
 115. **Figure 107**  
 116. **Figure 108**  
 117. **Figure 109**  
 118. **Figure 110**  
 119. **Figure 111**  
 120. **Figure 112**  
 121. **Figure 113**  
 122. **Figure 114**  
 123. **Figure 115**  
 124. **Figure 116**  
 125. **Figure 117**  
 126. **Figure 118**  
 127. **Figure 119**  
 128. **Figure 120**  
 129. **Figure 121**  
 130. **Figure 122**  
 131. **Figure 123**  
 132. **Figure 124**  
 133. **Figure 125**  
 134. **Figure 126**  
 135. **Figure 127**  
 136. **Figure 128**  
 137. **Figure 129**  
 138. **Figure 130**  
 139. **Figure 131**  
 140. **Figure 132**  
 141. **Figure 133**  
 142. **Figure 134**  
 143. **Figure 135**  
 144. **Figure 136**  
 145. **Figure 137**  
 146. **Figure 138**  
 147. **Figure 139**  
 148. **Figure 140**  
 149. **Figure 141**  
 150. **Figure 142**  
 151. **Figure 143**  
 152. **Figure 144**  
 153. **Figure 145**  
 154. **Figure 146**  
 155. **Figure 147**  
 156. **Figure 148**  
 157. **Figure 149**  
 158. **Figure 150**  
 159. **Figure 151**  
 160. **Figure 152**  
 161. **Figure 153**  
 162. **Figure 154**  
 163. **Figure 155**  
 164. **Figure 156**  
 165. **Figure 157**  
 166. **Figure 158**  
 167. **Figure 159**  
 168. **Figure 160**  
 169. **Figure 161**  
 170. **Figure 162**  
 171. **Figure 163**  
 172. **Figure 164**  
 173. **Figure 165**  
 174. **Figure 166**  
 175. **Figure 167**  
 176. **Figure 168**  
 177. **Figure 169**  
 178. **Figure 170**  
 179. **Figure 171**  
 180. **Figure 172**  
 181. **Figure 173**  
 182. **Figure 174**  
 183. **Figure 175**  
 184. **Figure 176**  
 185. **Figure 177**  
 186. **Figure 178**  
 187. **Figure 179**  
 188. **Figure 180**  
 189. **Figure 181**  
 190. **Figure 182**  
 191. **Figure 183**  
 192. **Figure 184**  
 193. **Figure 185**  
 194. **Figure 186**  
 195. **Figure 187**  
 196. **Figure 188**  
 197. **Figure 189**  
 198. **Figure 190**  
 199. **Figure 191**  
 200. **Figure 192**  
 201. **Figure 193**  
 202. **Figure 194**  
 203. **Figure 195**  
 204. **Figure 196**  
 205. **Figure 197**  
 206. **Figure 198**  
 207. **Figure 199**  
 208. **Figure 200**  
 209. **Figure 201**  
 210. **Figure 202**  
 211. **Figure 203**  
 212. **Figure 204**  
 213. **Figure 205**  
 214. **Figure 206**  
 215. **Figure 207**  
 216. **Figure 208**  
 217. **Figure 209**

The above-described embodiment is merely an exemplary embodiment, many other embodiments are possible.

2023.06.19.10:49:50